DatagraphiX. brings an end to the 80 column squeeze.

See how easy it reads at only 50% of actual size.

You're looking at 132 columns displayed on a single line with the Datagraphix 132A terminal-132 columns to end the 80 column squeeze

COUNT THEM!

Now DatagraphiX offers an alphanumeric interactive terminal that brings 132-column compatibility to your data processing operation.

The result of more than 20 years' experience in display technology, the DatagraphiX Model 132A terminal provides important savings in paper printout, programming, communication and processing while increasing efficiency through direct access.

This unique microprocessor-controlled display is enhanced by easy to read, high resolution Charactron® characters, and other operational features that bring new levels of versatility and convenience to you, the on-line user.

132A SYSTEM SPECIFICATIONS

	DISPLAY		FEATURES	
	Format	132 characters × 30 lines	Logic	Microprocessor — PROM
	Area	11 in. (28cm) wide \times 8 in. (20cm) high	Cursor	Up, down, left, right, home —
	Characters	96 Upper & lower case, ASCII	Edition of	addressing/sensing — Standard blink Character insert/delete
	Companyate di bu	Characters, OCR-B font	Editing	Line insert/delete
	Generated by	Charactron shaped beam CRT	Scroll	Up, down
	Font Size	0.1 in. (.25cm) high \times .06 in. (.15cm) wide	Tabbing	132 horizontal positions w/keyboard
	Intensities	Two, adjustable	Communication	display indicator
	Refresh Rate	60 Hz (50 Hz optional)		Character, line, message (length selectable by keyboard controls)
	Phosphor	P31, green		Computer control of all keyboard
	Resolution	Equivalent to more than 4,000 TV raster lines		functions
				Internal or external clocking
	KEYBOARD		Alarm	Audio tone w/volume control
	Style	Typewriter, 75 keys	Repeat	Automatic for cursor, editing and scroll
	Switching	Solid state (Hall effect)		w/key depressed
	Indicators	Ready, break, attention		Separate repeat key for all other functions
	Col. Counter	3-digit LED display	Highlight Higher intensity for line on which cursor is positioned — Moves w/cursor	
	Controls	Message/line/character transmission mode		is positioned — Moves w/cursor
			OPTIONS	
		Automatic line feed	Buffer	16K character memory (120 lines)
		All upper case characters	Printer	RS232C interface to serial printer
		Local/remote operation		w/message length controls
	COMMUNICATIO	N	OVERALL DIMENSIONS	



18.5 in. (47cm)

31.5 in. (80cm)

17.5 in. (44cm)

75 lbs. (34kg)

24 in. (61cm)

18 in. (46cm)

DESK SPACE (Including keyboard)

Height

Depth

Width

Weight

Depth

Width

Half/full duplex switch selectable (echoplex or non-echoplex in full duplex)

110, 150, 300, 600, 1200, 2400, 4800,

Mode

Parity

Interface

POWER

Speed (BPS)

9600

Odd; even or none

RS232C, 20 ma current loop

115VAC, 3A, 60 Hz (230VAC, 50 Hz optional)